

ATTENZIONE - ATTENTION - ACHTUNG

- Per lo smontaggio degli utensili utilizzare sempre la chiave di contrasto come indicato nel manuale d'uso.
- For disassembly of the tools use always the contrast key as mentioned in the user instructions.
- Fuer das Abmontieren der Werkzeuge immer den Gegenschlüssel benutzen wie in der Bedienungsanleitung erwaeht.

• Chiave inclusa

• Key included

• Schluessel inbegriffen

Cod. MT	Cod. MORI-SEIKI	Mandrino Spindle Spindel	I	RPM	Coppia Max Max Torque Max Drehmoment	Lubrificazione int. Coolant through Innenkuehlung	Lubrificazione est. Ext. coolant Aussenkuehlung	A	A1	B	D	L	CHIAVI NON INCLUSE Keys not included Schluessel nicht einbegriffen
M0141425	T32407	ER25	1:1	6000	40Nm	-	X	80.16	-	48	-	-	CHUB38 CHSTER25
M0141525	-	ER25	1:1	6000	40Nm	P=70bar	X	80.16	-	59	-	-	CHUB38 CHSTER25
M0141617	-	Ø16x17	1:1	6000	40Nm	-	X	-	63	48	16	17	CHUB36 CH_VTCROCE_M08 •
M0142219	-	Ø22x19	1:1	6000	40Nm	-	X	-	63	48	22	19	CHUB36 CH_VTCROCE_M10 •
M0142721	-	Ø27x21	1:1	6000	40Nm	-	X	-	65.5	48	27	21	CHUB36 CH_VTCROCE_M12 •

DMG-MORI


MOD: ZT1000/1500 12/16 STAZIONI

MODULO MOTORIZZATO ASSIALE PER CONTROMANDRINO H=65mm

Axial driven tool sub spindle side H=65mm

Axial angetriebenes Werkzeug fuer Gegenspindel H=65mm

Subject to change without notice.



M.T. srl

Via Casino Albini 480
Tel. 0541/956034-957884
Fax 0541/956341
47842 S. GIOVANNI IN M. (RN)
e-mail: mtma@mtmarchetti.com
http://www.mtmarchetti.com



PAGINA MZT155-1-10

09/2023