



Ball Valves



- Compact design is ideal for a wide variety of machining applications.
- Use with water-based coolants, oil or air (also vacuum applications)
- Corrosion resistant chrome-plated brass ■ Teflon Seals ■ Rated to 250 psi (16 bar) max

DIMENSIONS IN INCHES (except as noted)

| Part No. | Pipe Thread | L | N | H | B Hex | d Flow \varnothing | Handle Color | Pkg Qty | Configuration |
|----------|-------------|------|-----|-----|-------|----------------------|--------------|---------|---------------|
| BV19401 | 1/8 NPTF | 1.45 | .86 | .74 | 14mm | .21 | Blue | 2 | |
| BV19402 | 1/4 NPTF | 1.70 | .86 | .74 | 14mm | .21 | Blue | 2 | |
| BV19403 | 3/8 NPTF | 1.89 | .92 | .74 | 18mm | .31 | Blue | 2 | |
| BV19411 | 1/8 BSPT | 1.42 | .86 | .74 | 14mm | .21 | Red | 2 | |
| BV19412 | 1/4 BSPT | 1.70 | .86 | .74 | 14mm | .21 | Red | 2 | |
| BV19413 | 3/8 BSPT | 1.81 | .92 | .74 | 18mm | .31 | Red | 2 | |

Material: Body: Chrome-plated Brass Seals: Teflon **Max Pressure:** 250 psi (33 bar)

Maximum Operating Temperature: 175° F (80° C)